

Electronic Auto Drain Timer

Application

- Compressor Pneumatic System
- Seperator
- Air Dryer
- Air Receiver tank



Drain Timer



PU225+Timer

Features

- High Quality , Low cost

Timer

| | |
|-------------------------------|---------------------------------|
| Off Interval Time | : 0.5 - 45 minutes (adjustable) |
| On Interval Time | : 0.5 - 10 seconds (adjustable) |
| Manual Test Switch | : Micro Switch |
| Supply Voltage | : 24-240V AC/DC 50/60Hz |
| Supply Consumption | : 4 mA max. |
| Temperature Protection | : -40C ... +60C |
| Protection Class | : IP65 |
| Housing Materail | : Abs Plastic |
| Design Standard | : VDE 01 10C |

Drain Valve

| | |
|------------------------------|-------------------------|
| Type | : 2/2 way direct acting |
| Port | : 1/2" |
| Body | : Brass |
| Max. working pressure | : 16 Bar |
| Media Temperature | : 90C |
| Valve Seal | : Viton |
| Filter | : Yes |
| Protection Class | : IP65 , NEMA4X |
| Voltage Range | : +/- 10% |

Solenoid Valve PU225

| | |
|-----------------------------------|-------------------------|
| Type | : 2/2 way Pilot Operate |
| Port | : 1/2" , 3/4"& 1" |
| Body | : Brass |
| Max. working pressure | : 15 Bar |
| Operation working pressure | : 0.5 - 10Bar |
| Valve Seal | : NBR (-5C - 80C) |
| Insulation | : Class F |
| Protection Class | : IP65 , NEMA4X |
| Voltage Range | : +/- 10% |
| Coil | : DIN Type |
| Standard Current Voltage | : 220V |